# **RJ008 LETTERPLATE**

### **HEAVY DUTY**

Designed to meet the exacting security standards of TS 008:2015, the RJ008 letterplate is tested to withstand a series of physical tests based on the common methods of burglary. Providing up to 60 minutes fire resistance, this high-performance letterplate is available in a number of stylish finishes.







# Key benefits

- ▶ Tested to TS 008:2015
- No visible fixings
- ▶ Anti-vandal® feature
- > 37° opening to protect against 'key fishing'
- Quick and easy to install
- ▶ Can withstand thousands of openings
- > Smooth working mechanism.



**RJ008 Letterplate** 

### SYSTEM SPECIFICATIONS

### Test evidence

- Fire: BS 476-22:1987 in an FD30.
- Fire: BS 476-22:1987 in an FD60.
- Security: PAS 24:2016.
- Classified to TS 008:2015.
- Durability: 15,000 cycles.

### **Performance**

▶ Can provide up to 60 minutes fire resistance.

## Internal frame sizes

- Letterplate length: 300mm.
- Letterplate height: 115mm.
- Projection: 35mm.
- Frame material: Aluminium.

### **External frame sizes**

- Distance between screw holes: 277mm.
- Letterplate length: 305mm.
- Letterplate height: 77mm.
- Frame material: Aluminium.
- Mail aperture: 53mm x 260mm.

#### Door thickness

- 44mm timber door.
- ▶ 54mm timber door.

Aluminum outer casing with an intumescent lining.

#### Fixing

Please see product fitting instructions.

- ▶ Gold anodised aluminium.
- ▶ Silver anodised aluminium.
- Polished silver aluminium.

#### Accreditation

BSI certified for PAS 24:2016.



KM670828



certifire

