

# LVN20S

## HIGH PERFORMANCE NON-VISION FIRE + SMOKE DAMPER

The LVN20S provides a unique solution to the problem of containing both fire and smoke in emergency conditions yet offering good air transfer through doors in everyday use. Using the same intumescent louvred slat configuration as the LVN20, but incorporating an electro mechanically operated smoke shutter mechanism. Can provide up to 60 minutes fire and smoke resistance



FIRE + SMOKE RESISTANT AIR TRANSFER GRILLES

### Key benefits

- ▶ Contains cold smoke + toxic gases remote from source of fire
- ▶ Simple installation
- ▶ Auto reset + failsafe
- ▶ Safe low DC voltage
- ▶ Status reporting + auto-cycling via Talkback Damper Control Monitor (DCM)
- ▶ Optional audio warning facility
- ▶ Connects to fire panel +/- or BMS
- ▶ BMS alarm notification via Alarm Monitoring System (AMS)
- ▶ Nominal 5mA current open/closed
- ▶ Max 200mA in operation
- ▶ Allows bi-directional airflow
- ▶ Louvred slats give privacy.



LVN20S

### STANDARD SIZES AVAILABLE (MM)

WIDTH	198	248	298	348	398
HEIGHT	198	248	298	348	398

Other non-standard sizes may be available - please ask for details.

### SYSTEM SPECIFICATIONS

#### Test evidence

- ▶ Fire: BS 476-20 & 22: 1987.
- ▶ Smoke: BS 476-31.1: 1983 (shutterplate).

#### Performance

- ▶ Can be used to provide up to 60 minutes resistance to fire and cold smoke.

#### Size

- ▶ Width: 200mm - 400mm (in 50mm increments).
- ▶ Height: 200mm - 400mm (in 50mm increments).

#### Thickness

- ▶ 2 pieces x 20mm.

#### Free area

- ▶ Approx 30% free area.

#### Finish

- ▶ Silver as standard.

#### Application

- ▶ Suitable for doors.
- ▶ Please note: in applications where high levels of humidity or wetness are anticipated, please speak to our Technical Department for alternatives.

#### Orientation

- ▶ LVN20S must be used in the vertical plane.

#### Positional requirements

- ▶ The upper edge of the grille shall be no higher than 800mm from floor level.

#### Material

- ▶ Rigid PVC slats with an intumescent core.
- ▶ Steel flange.
- ▶ Electro mechanically operated smoke shutter mechanism.

#### Fixing

- ▶ Each damper is manufactured 2mm less than a nominal aperture size to provide clearance when installed in a duct or other aperture of the same nominal dimensions. e.g. a 198mm x 198mm nominal size damper will suit a 200mm x 200mm aperture.
- ▶ Screwed and bedded in Lorient intumescent sealant.

#### Use with

- ▶ Talkback damper control system.
- ▶ Conductor hinges.
- ▶ Optional Alarm Monitoring System (AMS) and battery backup.

#### Accreditation

